TECHNICAL BULLETIN



EverGreen® ULV 5-25 Air is a contact insecticide designed for aerial ULV applications. Formulated with botanically based pyrethrins and synergized with piperonyl butoxide (PBO) to kill mosquitoes on contact.

- Intended for use by mosquito abatement agencies
- Formulated with a higher density solvent for improved drift control and aerial targeting
- Includes more active ingredient per gallon for lower effective use rates, allowing for more treated acres per gallon

PRODUCT SPECIFICATIONS		
Key Target Pest(s)	Mosquitoes	
Signal Word	Caution	
Form	Concentrate	
Active Ingredient(s)	Pyrethrins; Piperonyl butoxide (PBO)	
Class of Chemistry	Pyrethrins (3A); Synergist	
Activity	Kills by contact	
Mode of Action	Sodium channel modulator; Interference with P-450 mediated detoxification system	
Stability	If frozen, thaw and shake before use	
Flammability	Not listed as flammable or combustible	
Odor	Sweet – solvent	
PPE Requirements	Long pants, long sleeves, shoes and socks, chemical resistant gloves, respirator (enclosed spaces)	
Maximum Yearly Application Rate	0.2 lbs. pyrethrins/acre, or 2.0 lbs. piperonyl butoxide/acre per year, whichever is lower	
Mix or Dilute In	Oil (optional)	
Shelf Life	3 years or more in ideal storage conditions	

Packaging

- 55 gallon drum
- 275 gallon tote

Use Sites

Outdoor Areas

- Agricultural
- Industrial
- Overgrown waste areas, roadsides and pastures
- Recreational
- Residential
- Swamps and marshes

Application Methods

Outdoor Areas

- Ultra-low volume (ULV)
 - By air
 - By ground



Best Practices When Using Evergreen ULV 5-25 Air

Evergreen ULV 5-25 Air may be applied undiluted or diluted with a suitable oil, such as (but not restricted to) light mineral oil, deodorized kerosene or petroleum distillate, for use in cold fog aerosol generators.

Recommended Equipment

- Aerial mounted sprayers:
 - Fixed wing
 - Rotary wing
 - Rotary Atomizer

- Ground equipment:
 - Backpack sprayers
 - Cold aerosol ULV generators
 - Thermal aerosol fogging equipment
 - Truck mounted ULV sprayers

Aerial Equipment

Spray equipment must be adjusted so that the volume median diameter (VMD) is less than 60 microns (Dv 0.5 < 60um) and that 90% of the spray is contained in droplets smaller than 80 microns (Dv 0.9 < 80um).

Release Height for Aerial

- Fixed wing: Apply using a nozzle height of no less than 100 feet above the ground or canopy.
- Rotary wing: Apply using a nozzle height of no less than 75 feet above the ground or canopy.

Ground Equipment

Spray equipment must be adjusted so that the volume median diameter (VMD) is less than 30 microns (Dv 0.5 < 30um) and that 90% of the spray is contained in droplets smaller than 50 microns (Dv 0.9 <50um).

Max. Daily Application Rates Lbs. Pyrethrins/Acre	FI. Oz of Evergreen ULV 5-25 Air per Acre
0.0025	0.67
0.008 (when targeting Aedes taeniorhynchus and other difficult species)	2.15

MGK Sustainability in Action

- Container is HDPE and 100% recyclable
- Shipping cartons and paper labels are sourced from Sustainably Managed Forests
- Formulated in a production facility that uses 100% renewable energy
- Our responsible sourcing of ingredients, like pyrethrum from Tanzania, supports long-term prosperity for smallholder farmers and drives economic growth in their communities
- Available in bulk, reducing packaging materials



Scan QR code or visit mgk.com/evergreen-ulv-5-25-air to see resources and additional information

Always read and follow all label instructions.

For any medical or safety questions, concerns, or incident reports, call 1-888-740-8712.

